



**ACADIAN INDUSTRIAL TEXTILES  
WOVEN CONTAINMENT FABRIC  
STYLE 11285**

Specifications

<b>FIBER CONTENT</b>	100% Polypropylene
<b>COLOR</b>	Black
<b>SHADE FACTOR</b>	85%
<b>CONSTRUCTION</b>	20 x 20
<b>WEIGHT ASTM D-5261</b>	4.7 oz/yd <sup>2</sup>
<b>TENSILE STRENGTH ASTM D-4632, Grab Method</b>	Warp: 252 lbs Fill: 250 lbs
<b>ELONGATION ASTM D-4632, Grab Method</b>	Warp: 17% Fill: 17%
<b>BURST STRENGTH ASTM D-3786</b>	414 lbs/in <sup>2</sup>
<b>PUNCTURE STRENGTH ASTM D-4833 Modified</b>	133.8 lbs
<b>TEAR STRENGTH ASTM D-2261, Trap Method</b>	Warp: 105 lbs Fill: 95 lbs
<b>AIR PERMEABILITY ASTM D-737</b>	637 cfm/ft <sup>2</sup>
<b>Solid yellow stripes are positioned as follows: 13” from each selvage and a center stripe is 62” from the selvage</b>	
The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.	