



**ACADIAN INDUSTRIAL TEXTILES
FIRE RETARDANT
WOVEN CONTAINMENT FABRIC
STYLE 11285W**

Specifications

FIBER CONTENT	100% Polypropylene
COLOR	White
SHADE FACTOR	48%
CONSTRUCTION	20 x 20
WEIGHT ASTM D-5261	4.72 oz/yd ²
TENSILE STRENGTH ASTM D-4632, Grab Method	Warp: 337 lbs Fill: 337 lbs
ELONGATION ASTM D-4632, Grab Method	Warp: 17% Fill: 17%
BURST STRENGTH ASTM D-3786	409 lbs/in ²
PUNCTURE STRENGTH ASTM D-4833 Modified	123.6 lbs
TEAR STRENGTH ASTM D-2261, Trap Method	Warp: 78bs Fill: 68bs
AIR PERMEABILITY ASTM D-737	312 ft ³ /min/ft ²
Solid black stripes are positioned as follows: 13” from each selvedge and a center stripe is 62” from the selvedge	
The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.	