



ACADIAN INDUSTRIAL TEXTILES
GROUND COVER FABRIC
PREMIUM L
STYLE 19284

Specifications

| | |
|---|--------------------------------|
| FIBER CONTENT | 100% Virgin Polypropylene |
| CONSTRUCTION | 22 x 10.5 |
| WEIGHT ASTM D-5261 | 3.0 oz/yd ² |
| TENSILE STRENGTH ASTM D-4632, Grab Method | Warp: 175 lbs Fill: 115 lbs |
| ELONGATION ASTM D-4632, Grab Method | Warp: 24% Fill: 20% |
| BURST STRENGTH ASTM D-3786 | 315 lbs/in ² |
| PUNCTURE STRENGTH ASTM D-4833 Modified | 76 lbs |
| TEAR STRENGTH ASTM D-4533, Trap Method | Warp: 75 lbs Fill: 60 lbs |
| WATER FLOW RATE ASTM D-4491 | 6 gal/min/ft ² |
| UV RESISTANCE, STRENGTH RETAINED UV Inhibitor – 2% Carbon Black | 70% at 2,500 hrs |

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.

TECHNICAL DATA SUPPLIED BY SGI TESTING