



**ACADIAN INDUSTRIAL TEXTILES**  
**GROUND COVER FABRIC**  
**PREMIUM B**  
**STYLE 15284**

Specifications

<b>FIBER CONTENT</b>	100% Virgin Polypropylene
<b>CONSTRUCTION</b>	20 x 10
<b>WEIGHT</b> ASTM D-3776	3.0 oz/yd <sup>2</sup>
<b>TENSILE STRENGTH</b> ASTM D-4632, Grab Method	Warp: 90 lbs Fill: 60 lbs
<b>ELONGATION</b> ASTM D-4632, Grab Method	Warp: 15% Fill: 15%
<b>BURST STRENGTH</b> ASTM D-3786	270 lbs/in <sup>2</sup>
<b>PUNCTURE STRENGTH</b> ASTM D-4833 Modified	72 lbs
<b>TEAR STRENGTH</b> ASTM D-2261, Trap Method	Warp: 64 lbs Fill: 50 lbs
<b>WATER FLOW RATE</b> ASTM D-4491	15.5 gal/min/ft <sup>2</sup>
<b>UV RESISTANCE, STRENGTH RETAINED</b> UV Inhibitor – 2% Carbon Black	70% at 2,500 hrs

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.