



## CONTAINMENT FABRIC SPECIFICATIONS

<b>Style #</b>	<b>11285</b>
<b>SHADE</b>	85%
<b>FIBER CONTENT</b>	100% Polypropylene
<b>COLOR</b>	Black
<b>CONSTRUCTION</b>	20 x 20
<b>WEIGHT</b> (ASTM D-5261)	4.7 oz/yd <sup>2</sup>
<b>TENSILE STRENGTH</b> (ASTM D-4632, Grab Method)	Warp: 251 lbs Fill: 250 lbs
<b>ELONGATION</b> (ASTM D-4632, Grab Method)	Warp: 17% Fill: 17%
<b>PUNCTURE STRENGTH</b> (ASTM D-4833, Modified)	133.8 lbs
<b>TEAR STRENGTH</b> (ASTM D-4533, Trap Method)	Warp: 105 lbs Fill: 95 lbs
<b>BURST STRENGTH</b> (ASTM D-3786)	414 psi
<b>AIR FLOW RATE</b> (ASTM D-737)	309 CFM
<p>The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent. Product specifications are typical average values and are subject to change.</p>	

**U.V. INHIBITOR: HALS with Carbon Black**  
TECHNICAL DATA PROVIDED BY PRODUCING MILL