



## WOVEN POLYPROPYLENE TRUCK COVER FABRIC SPECIFICATIONS

Style #	10434	10434-TR	10446-TC
<b>FIBER CONTENT</b>	Polypropylene	Polypropylene	Polypropylene
<b>FINISH</b>	N/A	Calendered	Calendered
<b>COLOR</b>	Black	Black	Black
<b>CONSTRUCTION</b>	53 x 48	55 x 48	30 x 20
<b>WEIGHT</b> (ASTM D-3776)	7.8 oz/yd <sup>2</sup>	7.8 oz/yd <sup>2</sup>	6.4 oz/yd <sup>2</sup>
<b>THICKNESS</b>	31 MIL	20 MIL	14 MIL
<b>TENSILE STRENGTH</b> (ASTM D-4632, Grab Method)	Warp: 465 lbs Fill: 400 lbs	Warp: 465 lbs Fill: 400 lbs	Warp: 525 lbs Fill: 290 lbs
<b>TEAR STRENGTH</b> (ASTM D-4553, Trap Method)	Warp: 185 lbs Fill: 165 lbs	Warp: 185 lbs Fill: 165 lbs	Warp: 150 lbs Fill: 65 lbs
<b>BURST STRENGTH</b> (ASTM D-3786)	740 lbs/in <sup>2</sup>	700 lbs/in <sup>2</sup>	550 lbs/in <sup>2</sup>

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.

**UV Inhibitors: Carbon Black**  
TECHNICAL DATA PROVIDED BY PRODUCING MILL