

## LENO WOVEN HDPE NETTING SPECIFICATIONS

Style #	10230-LL
FIBER CONTENT	High Density Polyethylene
SHADE	30%
CONSTRUCTION	13 x 13
WEIGHT (ASTM D-3776)	2.2 oz/yd²
TENSILE STRENGTH (ASTM D-5035, Strip Method)	Warp: 91 lbs Fill: 82 lbs
ELONGATION (ASTM D-5035, Strip Method)	Warp: 26% Fill: 18%
BURST STRENGTH (ASTM D-6241)	232 psi
TRAPEZOIDAL TEAR STRENGTH (ASTM D-4533)	Warp: 40 lbf Fill: 34 lbf
AIR PERMEABILITY @ 12.4 MPH (ASTM D-737)	1,004 CFM/SF

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.

UV INHIBITOR: HALS W/ CARBON BLACK
TECHNICAL DATA PROVIDED BY PRODUCING MILL