

BENIPLAST GREENHOUSE CURTAIN SPECIFICATIONS

Style #	10253-GH
MATERIAL	Woven HDPE w/ LDPE Lamination
TOTAL WEIGHT* (ASTM D-7336)	5.3 oz/yd ²
TENSILE STRENGTH (ASTM D-5035)	Warp: 157.4 lbf Weft: 202.3 lbf
ELONGATION (ASTM D-5035)	Warp: 20% Weft: 20%
PUNCTURE STRENGTH (ASTM D-6241)	438.4 lbf
TEAR STRENGTH (ISO 6383-1)	Warp: 87.7 lbf Weft: 66.4 lbf
COLOR *	Transparent
SHADE*	18%
LIGHT TRANSMISSION* (ASTM D-1003)	82%
DIFFUSION* (ASTM D-1003)	35%

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.

***Customization available. Call to Discuss. IR/Anti-Drip also available.**

UV INHIBITOR: HALS

TECHNICAL DATA PROVIDED BY PRODUCING MILL.

Performance properties affected if fabric installed near Sulfur, PVC or damaging chemicals.

Dimension	Stocked	Available
Widths	144"	20m (6.5') to 5.2m (17')
Length	400 Yard	Up to 1,000 m (1,090 yards)

Acadian, Inc. is the Exclusive North America Provider of:

