



## CONTAINMENT FABRIC SPECIFICATIONS

<b>Style #</b>	<b>10285-SB</b>
<b>FIBER CONTENT</b>	Polypropylene
<b>COLOR</b>	Black
<b>CONSTRUCTION</b>	20 x 20
<b>SHADE</b>	88%
<b>WEIGHT</b> (ASTM D-3776)	4.7 oz/yd <sup>2</sup>
<b>TENSILE STRENGTH</b> (ASTM D-5035, Strip Method)	Warp: 308 lbs Fill: 286 lbs
<b>ELONGATION</b> (ASTM D-5035, Strip Method)	Warp: 19% Fill: 17%
<b>BURST STRENGTH</b> (ASTM D-6241)	697 psi
<b>TRAPEZOIDAL TEAR STRENGTH</b> (ASTM D-4533)	Warp: 99 lbf Fill: 90 lbf
<b>AIR PERMEABILITY</b> <b>@ 12.4 MPH</b> (ASTM D-737)	79 CFM/SF
<p>The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.</p>	

**U.V. INHIBITOR: HALS W/ CARBON BLACK**  
TECHNICAL DATA PROVIDED BY PRODUCING MILL