



**CONTAINMENT FABRIC SPECIFICATIONS**

<b>Style #</b>	<b>10285-SB</b>
<b>SHADE</b>	88%
<b>FIBER CONTENT</b>	100% Polypropylene
<b>COLOR</b>	Black
<b>CONSTRUCTION</b>	20 x 20
<b>WEIGHT</b> (ASTM D-5261)	4.7 oz/yd <sup>2</sup>
<b>TENSILE STRENGTH</b> (ASTM D-4632, Grab Method)	Warp: 251 lbs Fill: 250 lbs
<b>ELONGATION</b> (ASTM D-4632, Grab Method)	Warp: 17% Fill: 17%
<b>PUNCTURE STRENGTH</b> (ASTM D-4833, Modified)	133.8 lbs
<b>TEAR STRENGTH</b> (ASTM D-4533, Trap Method)	Warp: 105 lbs Fill: 95 lbs
<b>BURST STRENGTH</b> (ASTM D-3786)	414 psi
<b>AIR FLOW RATE</b> (ASTM D-737)	309 CFM
<p>The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.</p>	

**U.V. INHIBITOR: HALS with Carbon Black**  
TECHNICAL DATA PROVIDED BY PRODUCING MILL