



CONTAINMENT FABRIC SPECIFICATIONS

Style #	10285-SB
FIBER CONTENT	Polypropylene
COLOR	Black
CONSTRUCTION	20 x 20
SHADE	88%
WEIGHT (ASTM D-3776)	4.7 oz/yd ²
TENSILE STRENGTH (ASTM D-5035, Strip Method)	Warp: 308 lbs Fill: 286 lbs
ELONGATION (ASTM D-5035, Strip Method)	Warp: 19% Fill: 17%
BURST STRENGTH (ASTM D-6241)	697 psi
TRAPEZOIDAL TEAR STRENGTH (ASTM D-4533)	Warp: 99 lbf Fill: 90 lbf
AIR PERMEABILITY @ 12.4 MPH (ASTM D-737)	79 CFM/SF
<p>The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.</p>	

U.V. INHIBITOR: HALS W/ CARBON BLACK
TECHNICAL DATA PROVIDED BY PRODUCING MILL