



MULTI-MESH FABRIC SPECIFICATIONS

Style #	19951-MM
FIBER CONTENT	Polyester
FINISH	Vinyl Coated
COLOR	Multi
CONSTRUCTION	24 x 12
DENIER	500D x 1,000D
WEIGHT (ASTM D-3776)	11.6 oz/yd ²
TENSILE STRENGTH (ASTM D-5035, Strip Method)	Warp: 380.8 lbf Fill: 376.5 lbf
ELONGATION (ASTM D-5035, Strip Method)	Warp: 27.3% Fill: 23.3%
TRAPEZOIDAL TEAR STRENGTH (ASTM D-4533)	Warp: 62.4 lbf Fill: 57.7 lbf
<p>The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.</p>	

UV ABSORBER: BENZOPHENONE
TECHNICAL DATA VERIFIED WITH 3rd PARTY TESTING.